

ANDEROL PRODUCT DATA SHEET

ANDEROL[®] 500H

SYNTHETIC COMPRESSOR OIL (ISO 100)

GENERAL INFORMATION

ANDEROL 500H is an ISO 100 diester-based lubricant designed to provide high temperature and long-term lubrication with minimal deposit formation.

ANDEROL 500H is rated H2 for use in food processing plant applications.

TYPICAL PROPERTIES:

SALES SPECIFICATIONS				
PROPERTY	TEST METHOD	MIN	MAX	TYPICAL RESULTS
Viscosity @ 40°C, cSt	ASTM D-445	90	110	98.8
Viscosity @ 100°C, cSt	ASTM D-445	---	---	10.4
Pour Point, °C	ASTM D-97	---	-25	-35
Flash Point, °C	ASTM D-92	230	-	240
Specific Gravity, 15.6°C	ASTM D-4052B	0.95	0.97	0.96

ADDITIONAL INFORMATION		
PROPERTY	TEST METHOD	TYPICAL RESULTS
Autoignition Temperature, °C	ASTM E-659	410
Conradson Carbon Residue, %	ASTM D-189	0.02
Evaporation, 22 hrs @ 99°C, %	ASTM D-972	<1.0
Copper Strip Corrosion, 3 hrs @ 100°C	ASTM D-130	1a
Demulsibility @ 54°C, ml oil/water/emulsion (minutes)	ASTM D-1401	39/38/3 (<60)
Four-Ball Wear, 1200 rpm, 75°C, 40 kg, 1 hr, mm	ASTM D-4172	0.8

ANDEROL 500H

APPLICATIONS

Cylinder and crankcase lubrication for reciprocating compressors, vane compressors and vacuum pumps for the following gases:

[®]ANDEROL is a reg. trademark of ANDEROL COMPANY.

This information is furnished without warranty, representation, inducement, or license of any kind, except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only chemists or chemically qualified lab technicians should carry out tests. Before using any chemical, read its label and Material Safety Data Sheet.

For more information please refer to the relevant Material Safety Data Sheet accompanying each product.

Air	Butadiene	Carbon Dioxide (dry)	Carbon Monoxide
Ethylene	Furnace (crack) Gas	Helium	Hydrogen
Hydrogen Sulphide (dry)	Methane	Natural Gas	Nitrogen
Propane	Synthesis Gas	Sulphur Hexafluoride	

ANDEROL® 500H may also be considered for other applications requiring an oxidation resistant lubricant. Nominal Operating Range is -15°C to 210°C (5°F to 410°F).

ADVANTAGES

- Fewer oil changes
- Reduces compressor maintenance
- Greatly reduces fire and explosion hazard
- Separates water condensate rapidly
- Lower oil consumption
- Eliminates lacquering and deposits
- Reduces energy consumption

APPROVALS

ANDEROL synthetic lubricants are the only long-life synthetic lubricants with over 30 years of successful performance. They are field tested, approved or recommended by major compressor manufacturers. Should you have any questions regarding the suitability of ANDEROL® 500H compressor lubricant for a specific manufacturer's model compressor, please check with your ANDEROL lubricant supplier or contact Anderol Company.

COMPATIBILITY


The following seals, paints, and plastics are recommended for use in contact with Anderol Company Synthetic Lubricants. Materials not recommended are also shown. For more information on other materials, see our "Compatibility Guide."

RECOMMENDED - Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT

NOT RECOMMENDED - Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS

A500c: 9/28/01 eb

 <p>DiveMiX gas & compressor technologies</p> <p>DiveMix Ltd. gas & compressor technologies PO Box 595 Abu Nawas Street, "Second Row" Hurghada, Red Sea, Egypt</p> <p>Phone: +20-65-3449056 Fax: +20-65-3449057 Email: Info@DiveMix.com Visit us at: www.DiveMix.com</p>	 <p>دايف ميكس التقنيات الغاز والخشب والخط</p> <p>دايف ميكس التقنيات الغاز والخشب والخط صندوق بريد 595 شارع ابو نواس - صنف ثاني الغردقة - البحر الاحمر - مصر</p> <p>تليفون: +٢٠-٦٥-٣٤٤٩٠٥٦ فاكس: +٢٠-٦٥-٣٤٤٩٠٥٧ بريد الكتروني: Info@DiveMix.com www.DiveMix.com موقعنا</p>
---	---



ANDEROL®
Specialty Lubricants

ANDEROL EMEA
Punterweg 21a
6222 NW Maastricht
Tel: +31-(0)43 352 4190
Fax: +31-(0)43 352 4199
E-mail: info@anderol-europe.nl